

**DISCONTINUED
LIMITED QTY
AVAILABLE**




Dimensions

Picture is a representation of actual product

Rated Capacity	A	B	C	D	E	F	G	H	I	J
lb/in										
25-500	2.81	1.30	0.62	0.26	0.25	0.50	1.81	1.00	1.00	0.50
kg/mm										
11.3-226.8	71.4	33.0	15.8	6.6	6.4	12.7	46.0	25.4	25.4	12.7

Order Information

Load Rating		Part#	Est. Weight	Price
25 lb	11.3 kg	53209	2 lb	Consult
50 lb	22.7 kg	53210	2 lb	Consult
75 lb	34.0 kg	53211	2 lb	Consult
100 lb	45.4 kg	53212	2 lb	Consult
150 lb	68.0 kg	53213	2 lb	Consult
250 lb	113.4 kg	53214	2 lb	Consult
500 lb	226.8 kg	53215	2 lb	Consult



Interchangeable Products

RICE LAKE WEIGHING SYSTEMS	
RL50210	page 139
RICE LAKE WEIGHING SYSTEMS	
RL60040SST	page 141
VPG SENSORTRONICS®	
60040	page 320
ARTECH®	
50210	—
VPG REVERE®	
5503	—

Weigh Module Available

RICE LAKE WEIGHING SYSTEMS	
RL50210 TA	page 52

Specifications

Full Scale Output:

3.0 mV/V

Bridge Resistance:

350 ohms, nominal

Material/Finish:

Stainless steel

Temperature:

Operating range
-40° F to 150° F/-40° C to 65° C

Safe Overload:

150% full scale

Rated Excitation:

5-10 VDC (15 V maximum)

Nonlinearity:

0.03% full scale

Hysteresis:

0.05% full scale

Insulation Resistance:

5,000 megohms

Deflection at Capacity:

25 lb-50 lb=0.008 in (0.20 mm)
100 lb=0.010 in (0.25 mm)
150 lb=0.012 in (0.30 mm)
250 lb=0.016 in (0.41 mm)
500 lb=0.025 in (0.64 mm)

Seal Type:

Environmentally sealed stainless steel sleeve, IP67

Cable Length:

20 ft (6.1 m)

Cable Diameter:

0.200 PVC jacket

Cable Color Code:

Red+ Excitation
Black.....- Excitation
Green+ Signal
White- Signal

Warranty:

Two-year limited warranty